



96063003 – 30FMH2S5

The MH Series, multi-stage booster pump is designed to meet your pressure boosting needs. The stainless steel construction offers high performance in a wide variety of applications. The MH Series is offered in five flow rates, 3-phase options, and horsepower sizes up to 7.5HP to make sure you have the right pump to fit your application.

Item: 96063003

Model: 30FMH2S5

Ratings

HP 60Hz	2 hp
Frequency	60 Hz
Phases	Single-Phase
Volts	115 VAC / 230 VAC
Motor	Surface
Protection [IP]	Not Applicable
Input Phase	Single-Phase
S.F.	1.25
Amps at 230 Volts	12 A
Service Factor - 50Hz	1

Operation

Flow	30 gpm
Minimum Head - 60 Hz	122 ft
Shut Off 60 Hz	279 ft
Stages	5
Motor Enclosure	ODP
Motor Cooling	Air

Liquid

Maximum Fluid Temperature	225 °F
---------------------------	--------

Materials of Construction

Pump Body Material	AISI 304 Stainless Steel
Impeller	Closed
Impeller Material	Stainless Steel
Discharge Material	Stainless Steel
Seal Material	Carbon/Ceramic, FKM, 300 series S.S.
Stage Housing Diffuser Material	Stainless Steel 304
Suction Material	Stainless Steel

Dimensions

Discharge	Threaded - FNPT
Discharge Diameter	1 "
Suction Diameter	1.25 "
Suction	Threaded - FNPT
Pump Length	21.64 "
Product Weight	41 lb
Product Weight with Pack	41.5 lb
Carton Length	24 mm
Carton Width	10 mm
Carton Height	10.88 "
Pump Height	8 "
Pump Width	7 "