

Qty.	Description
1	<p data-bbox="345 453 483 474">UPS 15-58 FRC</p> <div data-bbox="391 489 597 730">  </div> <p data-bbox="646 720 1003 741" style="text-align: center;">Note! Product picture may differ from actual product</p> <p data-bbox="345 743 548 764">Product No.: 59896343</p> <p data-bbox="345 766 743 877">The pump is of the canned rotor type, i.e. pump and motor form an integral unit without shaft seal and with only two gaskets for sealing. The bearings are lubricated by the pumped liquid. The pump has 3-step speed selector.</p> <p data-bbox="345 879 597 900">The pump is characterized by:</p> <ul data-bbox="375 903 760 1014" style="list-style-type: none"> * Ceramic shaft and radial bearings. * Carbon axial bearing. * Stainless steel rotor can and bearing plate. * Corrosion-resistant impeller, Composite. * Cast iron pump housing. <p data-bbox="345 1041 695 1083">The motor is a 1-phase motor. No additional motor protection is required.</p> <p data-bbox="345 1110 743 1222">Liquid: Pumped liquid: Water Liquid temperature range: 35.6 .. 230 °F Selected liquid temperature: 140 °F Density: 61.35 lb/ft³</p> <p data-bbox="345 1249 743 1339">Technical: Rated flow: 8.5 US GPM Rated head: 10.47 ft Approvals: UL, CSA</p> <p data-bbox="345 1367 808 1457">Materials: Pump housing: Cast iron EN 1561 EN-GJL-150 ASTM A48-25B</p> <p data-bbox="345 1459 743 1501">Impeller: Composite PES+30% GF</p> <p data-bbox="345 1528 792 1738">Installation: Maximum ambient temperature: 104 °F Amb. max at 80 dgr C liquid: 176 °F Maximum operating pressure: 145.04 psi Type of connection: 2-BOLT FLANGE R C.I. Flange Pipe connection: 2-BOLT FLANGE R Pressure rating for connection: PN 10 Port-to-port length: 6.54 in</p> <p data-bbox="345 1766 727 1808">Electrical data: Power input in speed 1: 0.0805 HP</p>